

## TECHNICAL FILE

**weber.color rústico**

---

**USES**

- Mortar used for joints 6 to 30 mm, on pavements and revetments. Interior and Exterior
- To be applied over: Cement based supports

**COMPOSITION**

White or Grey cement, siliceous sands, organic additives and pigment minerals.

**TECHNICAL DATA**

- ✓ Rest time after kneading: 2 minutes
- ✓ Pot life: Approximately 1 hour
- ✓ Adjustability time: 30 minutes
- ✓ Cleaning time: 3 hours
- ✓ Drying time: 5 hours
- ✓ Waiting time before circulation: 24 to 48 hours

The times indicated, obtained in normal environmental conditions, may increase with low temperatures and decrease with elevated temperatures.

- ✓ Density of mixture: 1,79
- ✓ Compressive resistance: > 100 kg/cm<sup>2</sup> (10 MPa)
- ✓ Flexural resistance: > 30 kg/cm<sup>2</sup> (3 MPa).
- ✓ Elasticity module: 12000 MPa.
- ✓ Capillarity: < 1 g/dm<sup>2</sup>min<sup>1/2</sup>.
- ✓ Retraction: <1.5 mm/m.

These test results were obtained under normal conditions, and may vary depending on the conditions of application.

**SUPPORT PREPARATION**

- The joints must be dry and clean of all dust.
- Before grouting, it is advisable waiting 24 to 48 hours of the placement of the tiles.
- On porous tiles, before grouting, protect with protector 060, to prevent spotting.

## **APPLICATION**

- Mix **weber.color rústico** with 4 liters of clean water per bag of 25 kgs, with an electrical mixer on slow speed.
- Apply mortar with a mason's spoon, applying pressure to insure that the joint gets completely filled.
- Once hardening initiates, or being, when the shine disappears from the surface of the mortar, cleaning may begin with a humid sponge. After 24 hours carry out a general cleaning.

## **Recommendations**

- Apply on small surface and clean progressively.
- Respect the amount of water added to the mixture, **weber.color rústico** is not to be "milky".
- **weber.color rústico** has a consistency of a traditional mortar.
- Do not apply during rainy or humid weather, or risk of freezing or direct insulation.
- Do not use excessive water when cleaning, avoiding the dispersion of the pigment and carbonation process.
- Do not use strong acids for cleaning.

## **Packaging:**

25 kg bags in pallets of 1400kg

## **Coverage:**

Depending on tile size and width

## **Color :**

see color chart

## **Storage and Shelf Life:**

12 months from the date of manufacture, in original closed package and protected from humidity.

